

Typical chemical and physical properties

ADDAPT® Foamstop 150N is a highly effective **water soluble** Foam Control Agent for all types of aqueous systems, especially suitable for curtain coating- and spray applications.

It is a proprietary blend of polyacrylates, PAGs and surface-active components.

All constituents are EINECS registered and comply with the FDA regulation (incidental contact with foodstuff)

Appearance	turbid liquid
Viscosity at 20 °C	15-300 mPa.s
Density at 20 °C	1.00-1.10 g/ml
Flash point	> 120 °C
FDA-no	21 CFR § 173.340

Applications and typical treat level recommended

Paint industry	0.05 to 0.5 % wt. on total formulation
Printing Ink industry	0.05 to 0.5 % wt. on total formulation
Floor polish- and cleaner industry	
Aqueous hydraulic fluids	
Aqueous metal working fluids	
Galvanic baths	

Benefits

- 100% solubility in water; no turbidity or haze of the liquid phase in clear systems
- Maintains the defoaming properties over a prolonged period of time
- Filters and spray nozzles will not be blocked whilst using ADDAPT® Foamstop 150N
- Effective over a wide pH range (6 to 12)
- Biodegradable
- Does not contain mineral oil, amines, nitrates or fluorides
- Metal surfaces are readily cleaned by rinsing with tap water
- No paint or plating adhesion problems expected when the defoamer is applied
- For use in formulations which contain non-ionic or anionic surfactants

Cautions

do not use in cationic systems

ADDAPT[®] Foamstop 150N

Safety and Handling	Please read Material Safety Data Sheet (MSDS) before handling.
Product Specification	This information is available on request through our local representative.
Packaging	This information is available on request through our local representative.
Storage Stability	At least 6 months at adequate storage

Quality Policy The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT[®] Chemicals BV is based on the principles of the NEN-EN-ISO-Standard 9001: 2008.

Liabilities

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.

ADDAPT Chemicals BV
Speltdijk 1
NL-5704 RJ Helmond
The Netherlands
Tel: + 31 - 492 - 59 75 75
Fax: + 31 – 492 - 55 29 55
E-mail: info@addapt-chem.com
Home page: <http://www.addapt-chem.com>

Publication Number FO82413
© ADDAPT Chemicals BV 2004
Version 3 : 2017