

Typical chemical and physical properties

ADDAPT® Foamstop 400F is a highly effective universal Foam Control Agent for water-based and solvent-based systems.

Proprietary blend of Poly-Alkylene Glycols and Surface-Active components.

Appearance	Slightly turbid liquid
Active content	100%
Viscosity at 25 °C	< 500 mPa.s
Density at 25 °C	1.01 - 1.05 g/cm ³
Flash point	> 120 °C
Mineral oil content	0 %
FDA-no	21 CFR § 173.340

This information is intended as a guideline only. For specifications please consult the Certificate of Analyses.

Applications and typical treat level recommended

Paint industry	0.05 to 0.5 % wt. on total formulation
Printing Ink industry	0.05 to 0.5 % wt. on total formulation
Floor polish- and cleaner industry	
Aqueous metal working fluids	
Solvent based Systems	0.05 to 0.5 % wt. on total formulation
	- Clear Wood Lacquers
	- Alkyd Paints
	- Two-pack Epoxies
	- PU-Systems

Benefits

- Emulsify-able in water; no haze of the liquid phase in clear systems
- Good compatibility in a wide range of solvent-borne systems
- It maintains the defoaming properties over a prolonged period of time
- Filters and spray nozzles will not be blocked whilst using ADDAPT® Foamstop 400F
- Effective over a wide pH range (0 to 14)
- No paint or plating adhesion problems expected when the defoamer is applied

ADDAPT[®] Foamstop 400F

Safety and Handling	Please read Material Safety Data Sheet (MSDS) before handling.
Product Specification	This information is available on request through our local representative.
Packaging	This information is available on request through our local representative.

Quality Policy The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT[®] Chemicals BV is based on the principles of the NEN-EN-ISO-Standard 9001 : 2015.

Liabilities *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

ADDAPT Chemicals BV
Speltdijk 1
NL-5704 RJ Helmond
The Netherlands
Tel: + 31 - 492 - 59 - 75 - 75
Fax: + 31 - 492 - 55 - 29 - 55
E-mail : info@addapt-chem.com
Home page: <http://www.addapt-chem.com>

Publication Number FO82419
© ADDAPT Chemicals BV 2003
Version 3: 2019

