

Typical chemical and physical properties

ADDAPT® Foamstop 400N is a highly effective, **complete water-soluble** Foam Control Agent.

It is a proprietary blend of Polyalkyleneglycols and surface-active components

All constituents are EINECS registered and comply with the FDA regulation. (incidental contact with foodstuff)

Appearance	Light, turbid liquid
Viscosity at 20 °C	< 500 mPa.s
Density at 20 °C	1.01-1.05 g/ml
Flash point	> 120 °C
Mineral oil content	0 %
FDA-no	21 CFR § 173.340

This information is intended as a guideline only. For specifications please consult the Certificate of Analyses.

Applications and typical treat level recommended

Paint industry	0.05 to 0.5 % wt. on total formulation
Printing Ink industry	0.05 to 0.5 % wt. on total formulation
Floor polish industry	
Aqueous hydraulic fluids	
Aqueous metalworking fluids	
Cleaners	(pH-values > 10)
Acidic media	

Benefits

- 100% solubility in water; no turbidity or haze of the liquid phase in clear systems
- It maintains the defoaming properties over a prolonged period of time
- Filters and spray nozzles will not be blocked whilst using ADDAPT® Foamstop 400N
- Effective over a wide pH range (0 to 14) - designed for aqueous systems with extreme pH values (lower than 3 and greater than 10)
- Biodegradable
- Metal surfaces are readily cleaned by rinsing with tap water
- No paint or plating adhesion problems expected when the defoamer is applied

