

Typical chemical and physical properties

ADDAPT® Foamstop SL 100 is a highly effective and versatile Foam Control Agent. It can be used in **aqueous** and **non-aqueous** systems.

It is a Silicone Compound containing minerals.

| | |
|--------------------|----------------------------|
| Appearance | Translucent liquid |
| Active content | 100 % |
| Viscosity at 25 °C | > 1000 mPa.s |
| Density at 25 °C | 1.0-1.05 g/cm ³ |
| Freezing point | < 10 °C |
| Flash point | > 315 °C |
| Boiling point | > 300 °C |

This information is intended as a guideline only. For specifications please consult the Certificate of Analyses.

Applications and typical treat level recommended

| | |
|-----------------------|--------------|
| Paint industry | 10 - 100 ppm |
| Printing Ink industry | 10 – 100 ppm |
| Cutting Oils | 10 – 100 ppm |
| Epoxy Resin systems | 10 – 100 ppm |

Benefits

ADDAPT® Foamstop SL 100 can be applied neat or dispersed in organic solvents like:

| | | |
|-----------------|---------------|-------------------|
| Ethyl Acetate | MIBK | Toluene |
| Amyl Acetate | Kerosine | Xylene |
| 2-Ethyl Hexanol | White Spirits | Perchloroethylene |

ADDAPT® Foamstop SL 100 disperses easily, requiring only mild agitation.

Maintains the defoaming properties over a prolonged period of time

ADDAPT® Foamstop SL 100 prevents the formation of macro-foam and reduces the formation of micro-foam. When used in pigmented systems; it does not influence the recoatability.

2/3 of the amount should be added during the grinding stage, 1/3 during the 'let down' stage.

