

## Typical chemical and physical properties

ADDAPT® Foamstop VF 35N is a highly effective Foam Control Agent for **low VOC**-Emulsion systems based on PVAC, Styrene/Acrylics or pure Acrylics.

**It is a proprietary blend of oils with PAG's and surface active components - MOSH/MOAH free -**

All constituents comply with the FDA regulation (incidental contact with foodstuff)

Appearance	Yellowish Liquid
Active content	100 %
Grade	Food grade – incidental contact
Specific gravity at 25 °C	0.95-1.00 g/cm <sup>3</sup>
Viscosity at 25 °C	50-250 mPa.s
FDA regulation:	#173.340
Solubility	
Water	miscible
Mineral oil	emulsifiable

*This information is intended as a guideline only. For specifications please consult the Certificate of Analyses.*

## Applications and typical treat level recommended

Paint and plaster Industry	0.25 to 0.75 % wt. based on total formulation
Adhesive industry	0.25 to 0.75 % wt. based on total formulation
Lubricant industry	
Wastewater treatment	

## Benefits

ADDAPT® Foamstop VF 35N is recommended for the use in pigmented **low VOC**-Emulsion paints, as well as high gloss Emulsion based lacquers and also for Emulsion based Adhesives

ADDAPT® Foamstop VF 35N is easy emulsifiable. 2/3 of the amount should be added during the grinding stage, 1/3 during the 'let down' stage

Very suitable for cost effective, high PVC emulsion paints

Maintains the defoaming properties over a prolonged period of time

Does not contain Nonylphenol derivatives, silicones, amines, nitrates and fluorides

No inter-coat adhesion problems expected when the defoamer is applied.

# ADDAPT<sup>®</sup> Foamstop VF 35N

---

<b>Safety and Handling</b>	Please read Material Safety Data Sheet (MSDS) before handling.
<b>Product Specification</b>	This information is available on request through our local representative.
<b>Packaging</b>	This information is available on request through our local representative.

---

**Quality Policy**                      The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT<sup>®</sup> Chemicals BV is based on the principles of the NEN-EN-ISO-Standard 9001:2015.

---

**Liabilities**                              *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

ADDAPT Chemicals BV  
Speltdijk 1  
NL-5704 RJ Helmond  
The Netherlands  
Tel: + 31 - 492 - 59 - 75 - 75  
Fax: + 31 - 492 - 55 - 29 - 55  
E-mail: [info@addapt-chem.com](mailto:info@addapt-chem.com)  
Home page: <http://www.addapt-chem.com>

Publication Number FO82549  
© ADDAPT Chemicals BV 2007  
Version 34: 2020

