

Typical chemical and physical properties

ADDAPT[®] **Foamstop** VF 10N is a VOC-free Foam Control Agent for low VOC emulsion systems based on PVAC, Styrene/Acrylics and pure Acrylics.

It is a proprietary blend of components based on renewable resources!

All constituents comply with the FDA regulation (Incidental contact with foodstuff)

Appearance	yellow liquid
Active content	100 %
Density at 20 °C	0.90 – 0.98 g/ml
Flash point	> 125 °C
Solubility	
Water	miscible
Mineral oil	emulsifiable

This information is intended as a guideline only. For specifications please consult the Certificate of Analyses.

Applications and typical treat level recommended

Paint Industry	0.1 to 1.0% wt. based on total formulation
Adhesive industry	0.1 to 1.0 % wt. based on total formulation
(Flexo-) Printing Inks	
Floor polish industry	
Lubricant industry	
Wastewater treatment	

Benefits

ADDAPT[®] Foamstop VF 10N is recommended for the use in pigmented VOC free-Emulsion paints, (Flexo-) Printing Inks as well as clear lacquers and also for Emulsion based Adhesives

ADDAPT[®] Foamstop VF 10N is easy emulsifiable. 2/3 of the amount should be added during the grinding stage, 1/3 during the 'let down' stage

Very suitable for cost effective, high PVC emulsion paints, textured masonry coatings and renders/plasters (Putz).

Maintains the defoaming properties over a prolonged period of time

ADDAPT[®] Foamstop VF 10N does not contain Nonylphenol derivatives (APEO-free); silicones/siloxanes; amines; nitrates or fluorides.

No intercoat adhesion problems are expected when the defoamer is applied.

Safety and Handling	Please read Material Safety Data Sheet (MSDS) before handling.
Product Specification	This information is available on request through our local representative.
Packaging	This information is available on request through our local representative.

Quality Policy The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT[®] Chemicals BV is based on the principles of the NEN-EN-ISO-Standard 9001: 2015.

Liabilities *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

ADDAPT Chemicals BV
Speltdijk 1
NL-5704 RJ Helmond
The Netherlands
Tel: + 31 - 492 - 59 - 75 - 75
Fax: + 31 - 492 - 55 - 29 - 55
E-mail: info@addapt-chem.com
Home page: <http://www.addapt-chem.com>

Publication Number FO82550
© ADDAPT Chemicals BV 2005
Version 4: 2017

