

**Typical chemical and physical properties**

ADDAPT® Foamstop WS 17 is a highly effective, **complete water-soluble** Foam Control Agent.

**It is a proprietary blend of Polyalkyleneglycols and surface-active components**

Appearance	Yellowish, slightly turbid liquid
Viscosity at 20 °C	< 75 mPa.s
pH	6.5 – 7.5
Density at 20 °C	1.05 – 1.15 g/cm <sup>3</sup>
Flash point	> 100 °C
Mineral oil content	0 %
FDA-no	21 CFR § 173.340

*This information is intended as a guideline only. For specifications please consult the Certificate of Analyses.*

**Applications and typical treat level recommended**

Paint industry	0.05 to 0.5 % wt. on total formulation
Printing Ink industry(Flexo Inks)	0.05 to 0.5 % wt. on total formulation
Floor polish industry	
Aqueous hydraulic fluids	
Aqueous metalworking fluids	
Cleaners/Detergents/Rinse Aids	0.1 to 0.75% wt. on total formulation
Acidic and Alkaline media	

**Benefits**

100% solubility in water; no turbidity or haze of the liquid phase in clear systems.

ADDAPT® Foamstop WS 17 is designed for aqueous systems with extreme pH values.

Effective over a wide pH range (1 to 13).

It maintains the defoaming properties over a prolonged period of time.

Filters and spray nozzles will not be blocked whilst using ADDAPT® Foamstop WS 17

Biodegradable.

Metal surfaces are readily cleaned by rinsing with tap water.

No paint or plating adhesion problems expected when the defoamer is applied.

# ADDAPT® Foamstop WS 17

---

<b>Safety and Handling</b>	Please read Material Safety Data Sheet (MSDS) before handling.
<b>Product Specification</b>	This information is available on request through our local representative.
<b>Packaging</b>	This information is available on request through our local representative.

---

**Quality Policy**                      The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN-EN-ISO-Standard 9001 : 2015

---

**Liabilities**                              *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

ADDAPT Chemicals BV  
Speltdijk 1  
NL-5704 RJ Helmond  
The Netherlands  
Tel: + 31 - 492 - 59 - 75 - 75  
Fax: + 31 - 492 - 55 - 29 - 55  
E-mail: [info@addapt-chem.com](mailto:info@addapt-chem.com)  
Home page: <http://www.addapt-chem.com>

Publication Number FO82600  
© ADDAPT Chemicals BV 2012  
Version 4: 2019

