

Typical chemical and physical properties

ADDAPT[®] WaxMul WM 110 is a wax emulsion based on a balanced blend of Polyethylene and Paraffin waxes giving water repellent properties as well as a matting effect.

It is an emulsion of Polyethylene and Paraffin waxes in water.

Appearance	Turbid liquid
Color	Colorless - Milky white
Surfactant system	Non ionic/Anionic
Solid content	30 -34 %
Melting point wax blend	50 - 110 °C
Viscosity, 20°C	<150 cSt
pH	9.0 – 10.0

Applications and typical treat level recommended

Paint industry	dosage: 1.5 - 2.5%
Printing Ink industry	dosage: 1.5 - 2.5%
Shoe and Leather Care	
Paper Industry	

Benefits

- Gives very good water-repellent properties
- Gives a Matt gloss
- Improves the surfaces smoothness
- ADDAPT[®] WaxMul WM 110 is APEO-free

ADDAPT[®] WaxMul WM 110

Safety and Handling	Please read Material Safety Data Sheet (MSDS) before handling.
Product Specification	This information is available on request through our local representative.
Packaging	This information is available on request through our local representative.

Quality Policy The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT[®] Chemicals Bv is based on the principles of the NEN-EN-ISO-Standard 9001: 2008.

Liabilities *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

ADDAPT Chemicals BV
Speltdijk 1
NL-5704 RJ Helmond
The Netherlands
Tel: + 31 - 492 - 59 - 75 - 75
Fax: + 31 - 492 - 55 - 29 - 55
E-mail: info@addapt-chem.com
Home page: <http://www.addapt-chem.com>

Publication Number W88913
© ADDAPT Chemicals BV 2003
Version 1: 2005

